



# **Material Safety Data Sheet**

# HAZARD WARNINGS RISK PHRASES PROTECTIVE CLOTHING Corrosive to eyes and skin on contact. Toxic compound, do not ingest or inhale. Avoid all contact with this material. Environmental hazard. This material is very toxic to aquatic organisms and may cause long term adverse effects to the aquatic environment. Air sensitive material.

Readily absorbed through skin.

Section I.	Chemical Product and Company Identification				
Chemical Name	N,N'-Di-sec-butyl-p-phenylenediamine				
Catalog Number	D2268	Supplier	TCI America 9211 N. Harborgate St.		
Synonym	1,4-Benzenediamine, N,N'-bis(1-methylpropyl)-(9CI)		Portland OR 1-800-423-8616		
Chemical Formula	C <sub>14</sub> H <sub>24</sub> N <sub>2</sub>				
CAS Number	101-96-2	In case of Emergency Call	Chemtrec® (800) 424-9300 (U.S.) (703) 527-3887		
			(International)		

Section II. Composition and Information on Ingredients					
Chemical N	Name	CAS Number	Percent (%)	TLV/PEL	Toxicology Data
N,N'-Di-sec-butyl-p-phenylenediamine		101-96-2	Min. 98.0 (GC)		Rat LD 50 (oral) 148 mg/kg Rabbit LD 50 (dermal) 2806 mg/kg Guinea Pig LD 50 (dermal) 5 g/kg

Section III.	Hazards Identification
Acute Health Effects	Corrosive to skin, eyes, and respiratory system. Liquid or spray mist may produce tissue damage, particularly in mucous membranes of the eyes, mouth and respiratory tract. Skin contact may produce burns. Eye contact can result in corneal damage or blindness. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Corrosive materials may cause serious injury if ingested.  Toxic if ingested or inhaled. Avoid prolonged contact with this material. Overexposure may result in serious illness or death.  Readily absorbed through skin.  Follow safe industrial hygiene practices and always wear proper protective equipment when handling this compound.
Chronic Health Effects	CARCINOGENIC EFFECTS: Not available.  MUTAGENIC EFFECTS: Not available.  TERATOGENIC EFFECTS: Not available.  DEVELOPMENTAL TOXICITY: Not available.  Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection. Repeated exposure to an highly toxic material may produce general deterioration of health by an arcumulation in one or many human organs.

Section IV.	First Aid Measures
Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Skin Contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
Inhalation	If the victim is not breathing, perform mouth-to-mouth resuscitation. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, oxygen can be administered. Seek medical attention if respiration problems do not improve.
Ingestion	DO NOT INDUCE VOMITING. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive.

D2268	N,N'-Di-sec-butyl-p-phenylenediamine Page 2				
Section V.	Fire and Explosion Data				
Flammability	May be combustible at high temperature.	Auto-Ignition	Not available.		
Flash Points	100°C (212°F).	Flammable Limits	Not available.		
Combustion Products	These products are toxic carbon oxides (CO, CO	<sub>2</sub> ), nitrogen oxides (NO, NO	2).		
Fire Hazards	Not available.				
Explosion Hazards	Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.				
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder.  LARGE FIRE: Use water spray, fog or foam. DO NOT use water jet.  Consult with local fire authorities before attempting large scale fire–fighting operations.				
Section VI.	Accidental Release Measu	ires			
Spill Cleanup Instructions	Corrosive material. Toxic material. Environmentally hazardous material. Air senstive material. Material is readily absorbed through skin.  Stop leak if without risk. If the product is in its solid form: Use a shovel to put the material into a convenient waste disposal container. If the product is in its liquid form: Absorb with DRY earth, sand or other non-combustible material. DO NOT get water inside container. Absorb with an inert material and put the spilled material in an appropriate waste disposal. DO NOT touch spilled material. Use water spray curtain to divert vapor drift. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all sources of ignition. Consult federal, state, and/or local authorities for assistance on disposal.				
Section VII.	Handling and Storage				
Handling and Storage Information	CORROSIVE. TOXIC. ENVIRONMENTAL HAZARD. AIR SENSITIVE. READILY ABSORBED THROUGH SKIN. Keep locked up. Keep container dry. Keep away from heat. Mechanical exhaust required. When not in use, tightly seal the container and store in a dry, cool place. Avoid excessive heat and light. DO NOT ingest. Do not breathe gas/fumes/ vapor/spray. Never add water to this product. Wear suitable protective clothing. If ingested, seek medical advice immediately and show the container or the label. Treat symptomatically and supportively.  Always store away from incompatible compounds such as oxidizing agents, acids.				
Section VIII.	Exposure Controls/Personal Protection				
Engineering Controls	Provide exhaust ventilation or other engin respective threshold limit value. Ensure that eyewash st		airborne concentrations of vapors below their othework-station location.		
Personal Protection	Face shield. Lab coat. Vapor respirator. Boots. Gloves. A MSHA/NIOSH approved respirator must be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.				
Exposure Limits	Not available.				
Section IX.	Physical and Chemical Properties				
Physical state @ 20°C	Liquid. (Pale Yellowish Red to Yellowish	Solubility	Soluble in Ethanol, Benzene,		
Specific Gravity	Red, Clear.) 0.94 (water=1)		Hydrocarbons. Insoluble in water.		
Molecular Weight	220.35	Partition Coefficient	Not available.		
Boiling Point	159°C (318.2°F) @ 7 mmHg	Vapor Pressure	Not available.		
Melting Point	18°C (64.4°F)	Vapor Density	Not available.		
Refractive Index	1.533 - 1.537	Volatility	Not available.		
Critical Temperature	Not available.	Odor	Not available.		
Viscosity	Not available.	Taste	Not available.		
Section X.	Stability and Reactivity D	ata			
Stability	This material is stable if stored under proper conditions. (See Section VII for instructions)				
Conditions of Instability	Sensitive to air. Avoid excessive heat and light.				
Incompatibilities	Reactive with strong oxidizing agents, strong acids.				

### Section XI. **Toxicological Information**

RTECS Number

SS9040000

Routes of Exposure

Eye Contact. Ingestion. Inhalation. Skin contact.

Toxicity Data

Rat LD 50 (oral) 148 mg/kg Rabbit LD 50 (dermal) 2806 mg/kg Guinea Pig LD 50 (dermal) 5 g/kg

Chronic Toxic Effects

CARCINOGENIC EFFECTS : Not available. MUTAGENIC EFFECTS TERATOGENIC EFFECTS **DEVELOPMENTAL TOXICITY**: Not available.

Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection. Repeated exposure to an highly toxic material may produce general deterioration of health by an

accumulation in one or many human organs.

Acute Toxic Effects

Corrosive to skin, eyes, and respiratory system. Liquid or spray mist may produce tissue damage, particularly in mucous membranes of the eyes, mouth and respiratory tract. Skin contact may produce burns. Eye contact can result in corneal damage or blindness. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Corrosive materials may cause serious injury if ingested.

Toxic if ingested or inhaled. Avoid prolonged contact with this material. Overexposure may result in serious illness or

death.

Readily absorbed through skin.

Follow safe industrial hygiene practices and always wear proper protective equipment when handling this compound.

### Section XII. **Ecological Information**

Ecotoxicity

Not available.

Environmental Fate

Not available.

### Section XIII. Disposal Considerations

Waste Disposal

Recycle to process, if possible. Consult your local regional authorities. You may be able to dissolve or mix material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber system. Observe all federal, state and local regulations when disposing of the substance.

### Section XIV. Transport Information

**DOT Classification** 

DOT Class 8: Corrosive material DOT Class 6.1: Toxic material

PIN Number

UN2922

Proper Shipping Name

Corrosive liquids, toxic, n.o.s.

Packing Group (PG)

**DOT Pictograms** 



### Section XV. Other Regulatory Information and Pictograms

TSCA Chemical Inventory (EPA)

ON the EPA Toxic Substances Control Act (TSCA) inventory list.

WHMIS Classification (Canada)

CLASS D-1B: Material causing immediate and serious toxic effects (TOXIC)

CLASS E: Corrosive liquid.

On DSL

EINECS Number (EEC)

202-992-2

**EEC Risk Statements** 

R23/24/25- Toxic by inhalation, in contact with skin and if swallowed.

R34- Causes burns.

R50- Very toxic to aquatic organisms.

R53- May cause long-term adverse effects in the aquatic environment.

Japanese Regulatory Data

ENCS No. 3-247

D2268

# N,N'-Di-sec-butyl-p-phenylenediamine

Page 4

## Section XVI. Other Information

Version 1.0 Validated on 2/22/2007. Printed 2/22/2007.

### Notice to Reader

TCI laboratory chemicals are for research purposes only and are NOT intended for use as drugs, food additives, households, or pesticides. The information herein is believed to be correct, but does not claim to be all inclusive and should be used only as a guide. Neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All chemical reagents must be handled with the recognition that their chemical, physiological, toxicological, and hazardous properties have not been fully investigated or determined. All chemical reagents should be handled only by individuals who are familiar with their potential hazards and who have been fully trained in proper safety, laboratory, and chemical handling procedures. Although certain hazards are described herein, we can not guarantee that these are the only hazards which exist. Our MSDS sheets are based only on data available at the time of shipping and are subject to change without notice as new information is obtained. Avoid long storage periods since the product is subject to degradation with age and may become more dangerous or hazardous. It is the responsibility of the user to request updated MSDS sheets for products that are stored for extended periods. Disposal of unused product must be undertaken by qualified personnel who are knowledgeable in all applicable regulations and follow all pertinent safety precautions including the use of appropriate protective equipment (e.g. protective elothing, breathing equipment, facial mask, fume hood). For proper handling and disposal, always comply with federal, state, and local regulations.

Printed 2/22/2007.